

Fiber optic cable - FVT

Deployment and installation type: designed for underground ducts, galleries or buried, where optimal fire performance and moderate rodent protection are required.

Cable type: fully dielectric cable, with fiberglass yarns as tensile reinforcement element, and flame retardant, low smoke and halogen free thermoplastic sheath (LSZH).

Fully dielectric: Cables are completely dielectric, eliminating the possibility of interferences with existing power lines or coaxial cables.

Optical Fiber: different types based on customer requirements.

Dry core: the use of waterblocking materials avoids water propagation through the cable.


Integrability: this solution can be complemented with the rest of TELNET FTTH portfolio: loose tube cables for trunk and access network, microcables, optical splitters, splice closures, drop cables, termination boxes and patchcords.

Construction detail

1. Dielectric Fiberglass Reinforced Plastic (FRP) as central strength member
2. PBT loose tubes containing optical fibers, and fillers (if required), stranded in SZ around the FRP, and coated with water-blocking material
3. Fiber glass yarns as tensile reinforcement element and moderate protection against rodents
4. Flame retardant, low smoke and halogen free thermoplastic sheath (LSZH)

Mechanical and physical features

	Test Method	Acceptance criteria
Max. Tensile load	IEC 60794-1-E1	3000 N
Crush resistance	IEC 60794-1-E3	20 N/mm
Impact resistance	IEC 60794-1-E4	5 J
Temperature cycle	IEC 60794-1-F1	-30°C / +70°C
Bending radius	IEC 60794-1-E11, proc. 1	15 x cable diameter
Water propagation	IEC 60794-1-F5	
Flame propagation	IEC 60332-2-2	
Halogen emission	IEC 60754-1	
Smoke density	IEC 61034-2	



Outer jacket marking (*)

TELNET-RI	Year	Num fibers	Fiber type	Cable type	Production order	Length
TELNET-RI	XXXX	XXX OF	XXX	FVT	OF-XXXXXXXX-E	XXXX

Color coding of fibers (1)

	1	2	3	4	5	6	7	8	9	10	11	12
Optical Fiber	A	Nj	V	M	Gr	B	R	N	Am	Vi	Rs	At

Color coding of tubes (1)

Number of fibers	1	2	3	4	5	6	7	8	9	10	11	12
12	A	N	N	N	N	N						
24	A	N	N	Nj	N	N						
36	A	N	Nj	N	V	N						
48	A	Nj	N	V	M	N						
60	A	Nj	V	M	Gr	N						
72	A	Nj	V	M	Gr	B						
96	A	Nj	V	M	Gr	B	R	N*				
144	A	Nj	V	M	Gr	B	R	N*	Am	Vi	Rs	At

A: Blue, Nj: Orange, V: Green, M: Brown, Gr: Grey, B: White, R: Red, N: Black, Am: Yellow, Vi: Violet, Rs: Pink, At: Turquoise

The tubes marked as "N" are fillers (without optical fiber)

The tubes marked as "N*" are tubes with optical fibers

Dimension, structure and weight (1)

OF per cable	Number of tubes/fillers	Number of fibers per tube	Nominal diameter (mm)	Nominal weight (Kg/Km)
12	1	5	12	11,4
24	2	4	12	11,4
36	3	3	12	11,4
48	4	2	12	11,4
60	5	1	12	11,4
72	6	0	12	11,4
96	8	0	12	12,6
144	12	0	12	15,4

Contact Information

TELNET Redes Inteligentes Headquarters

Polígono Industrial Centrovía
c/ Buenos Aires, 18
50198 La Muela, Zaragoza
Spain
Phone: (+34) 976 14 18 00
Fax: (+34) 976 14 18 10
telnet@telnet-ri.es

Commercial office in Madrid

Avda. Menéndez Pelayo, 85 - 1º A
28007 Madrid
Spain
Phone: (+34) 91 434 39 92
Fax: (+34) 91 434 40 84

Subsidiary in Portugal

NETIBERTEL
Av. Fontes Pereira de Melo, 35 - 14ºD
1050-118 Lisbon
Portugal
comercial.pt@telnet-ri.es

www.telnet-ri.es

(1) TELNET, as manufacturer, designs and manufactures cables according to customer requirements, offering additional configurations to the ones shown in datasheet. For further information, please contact TELNET.